



DITCH WITCH®

720ML MAGNETIC LOCATOR

With its rugged durability, unmatched sensitivity, and simple operation, the 720ML can help make sure you never miss a magnetic target again. So whether it's a marker stake, a manhole cover, a valve box, or a cast iron pipe, you'll locate it fast and get on with the job. Throw a Ditch Witch 720ML magnetic locator in the truck, and leave the guesswork at home.



KEY FEATURES

With only two controls located under the cover, the 720ML is designed for one-hand operation and rugged dependability.

Easy-to-read digital bar graph displays signal strength and polarity to help you pinpoint the target.

The 720ML comes with a choice of two audio modes to suit operator preference.

DETAILS

Offers more than 60 hours of operational life on just two lithium 9-volt batteries.

Four sensitivity settings allow you to customize the locator for your soil conditions.

Lightweight, easy-to-use design reduces operator training time and search time.

The rugged, high-performance 720ML is backed by an industry-exclusive seven-year warranty.

Comes standard with a custom case designed to withstand the rigors of field use.

Every 720ML magnetic locator is backed by superior quality service and support, all available from a worldwide network of Ditch Witch dealers.

720ML SPECIFICATIONS

| | |
|------------------------|--|
| OUTPUT | SIGNAL INCREASES OR DECREASES IN VOLUME WITH GRADIENT-FIELD INTENSITY. |
| AUDIO | SIGNAL INCREASES OR DECREASES IN FREQUENCY WITH GRADIENT-FIELD INTENSITY. |
| SWITCH AT A | DIGITAL READOUT AND EXPANDING BAR GRAPHS INDICATE POLARITY (+ OR -) AND RELATIVE STRENGTH OF |
| SWITCH AT B | THE MAGNETIC FIELD. |
| VISUAL | 60 HOURS (INTERMITTENT USAGE) |
| BATTERY LIFE | TWO LITHIUM 9-VOLT BATTERIES |
| INPUT POWER | 4-SEGMENT LCD BATT INDICATOR |
| BATTERY CHECK | 2.5 LB (1.14 KG) |
| WEIGHT | -13 TO 140°F (-25 TO 60°C) |
| OPERATING TEMPERATURE | 34.5 IN (875 MM) |
| OVERALL LENGTH | 21 IN (533 MM) |
| WATERPROOF LENGTH | 14 IN (355 MM) |
| NOMINAL SENSOR SPACING | MODULAR, ALL SOLID STATE |
| CONSTRUCTION | |

SPECIFICATIONS ARE GENERAL AND SUBJECT TO CHANGE WITHOUT NOTICE. IF EXACT MEASUREMENTS ARE REQUIRED, EQUIPMENT SHOULD BE WEIGHED AND MEASURED. DUE TO SELECTED OPTIONS, DELIVERED EQUIPMENT MAY NOT NECESSARILY MATCH THAT SHOWN.