



DITCH WITCH®

HT220 TRENCHER

The Ditch Witch line of trenchers just got bigger—a lot bigger. The HT220 is a rock-digging workhorse designed to thunder through extreme conditions that others wouldn't dare to. And with trenches up to 8 feet (2.4 m) deep and up to 24 inches (610 mm) wide, the HT220 will dig down deep and get the job done.



KEY FEATURES

Exclusive flywheel gearbox delivers maximum power to the trenching attachment on demand—while greatly reducing shockloads to the hydraulic system.

Forged, heat-treated, high-alloy steel headshaft is guaranteed for life.

Reversible spoils conveyor effectively deposits soils on either side of the trench.

Trencher stabilizers—which effectively isolate vibration in rock and other harsh conditions—are standard equipment.

DETAILS

Reliable cruise control system automatically adjusts ground speed to changing soil conditions.

Patented bit block digging system lets you easily customize your digging tooth pattern to best fit your application.

Easy-to-use controls are designed for optimal productivity and reliability in harsh job applications.

Fully enclosed cab with climate control greatly increases operator comfort, reduces noise, and comes standard on every machine.

Sturdy undercarriage is designed to withstand the rigors of rock-laden jobsites.

The Ditch Witch organization supports all of its products with superior-quality parts, service, and training, all available from a worldwide network of Ditch Witch dealers.



SPECIFICATIONS

HT220

DIMENSIONS

TRANSPORT HEIGHT
TRANSPORT LENGTH (WITH 6-FT/1.8-M BOOM
AND TRENCH CLEANER)
TRANSPORT WIDTH
WEIGHT, MAXIMUM

U.S.	METRIC
112 IN	2.8 M
27 FT 9 IN	8.45 M
85 IN	2.15 M
42,990 LB	19 500 KG

OPERATION

GROUND DRIVE SPEED, FORWARD
GROUND DRIVE SPEED, REVERSE
GROUND DRIVE TRANSMISSION

BRAKE

TRENCH DEPTHS
TRENCH WIDTHS
SINGLE CHAIN
DOUBLE CHAIN
DIGGING CHAIN SPEED

0 - 2.3 MPH	0 - 3.7 KM/H
0 - 2.3 MPH	0 - 3.7 KM/H
DUAL PATH, HYDROSTATIC DRIVE; PLANETARY TRANSMISSION	
INTEGRAL SPRING-APPLIED, PRESSURE- RELEASED, WET DISC BRAKE	
4 FT, 6 FT, 8 FT	1.2 M, 1.8 M, 2.4 M
12 - 18 IN	300 - 460 MM
20 - 24 IN	500 - 600 MM
0 - 650 FPM	0 - 200 M/MIN

CONVEYOR DRIVE

BELT SPEED
DISCHARGE DIRECTION
CONVEYOR LENGTH
CONVEYOR BELT WIDTH
CONVEYOR TRAVERSE

0 - 820 FPM	0 - 250 M/MIN
RIGHT OR LEFT	
79 IN	2.0 M
24 IN	600 MM
22 IN	550 MM

HYDRAULIC SYSTEM

TYPE
FLOW RATE, MAXIMUM
PRESSURE, MAXIMUM

PRESSURE AND FLOW COMPENSATED	
45 GPM	170 L/MIN
2600 PSI	180 BAR

POWER

ENGINE
FUEL
COOLING MEDIUM
INJECTION
ASPIRATION
NUMBER OF CYLINDERS
DISPLACEMENT
BORE
STROKE
NET POWER RATING PER SAE J1349
RATED SPEED

CUMMINS QSB5.9	
DIESEL	
LIQUID	
DIRECT	
TURBOCHARGED	
6	
359 CU IN	5.9 L
4.02 IN	102 MM
4.72 IN	120 MM
215 HP	160 KW
2250 RPM	2250 RPM

FLUID CAPACITIES

FUEL TANK
ENGINE OIL, INCLUDING FILTER
HYDRAULIC RESERVOIR

106 GAL	400 L
6.6 GAL	25 L
77 GAL	290 L

BATTERY

SAE RESERVE CAPACITY RATING
SAE COLD CRANK RATING @ 0°F (-18°C)

150 MIN	150 MIN
825 AMPS	825 AMPS

SPECIFICATIONS ARE GENERAL AND SUBJECT TO CHANGE WITHOUT NOTICE. IF EXACT MEASUREMENTS ARE REQUIRED, EQUIPMENT SHOULD BE WEIGHED AND MEASURED. DUE TO SELECTED OPTIONS, DELIVERED EQUIPMENT MAY NOT NECESSARILY MATCH THAT SHOWN. CONTAINS PATENTED FEATURES.