



Ditch Witch[®]
Performance Parts

Power Pipe[™]

Fluid Miser[™] II



- **Patented PVC liner that:**

- 1) **Reduces drilling fluid loss** by up to 82% during breakout, which saves fluid and clean-up costs.
- 2) **Reduces plugging of nozzles** by reducing rust in the drill pipe.
- 3) **Allows faster pressure-up** during the drilling process.



- **Larger tool joint outer diameter for more strength.**

- **Different steel types for extended life**

- 4140 premium steel used in tool pin and box
- High strength, proprietary, steel alloy used for pipe tube

- **Pin and box is a double shoulder design for maximum tool joint strength and reliability.**



Power Pipe™

Part #	Model	Savings		Pipe Length	Drill Tube Size	Bend Radius
		%	gal/100'			
369-048	JT920	79	3.9	6'-6" (2 m)	1.58 (40 mm)	105' (32 m)
369-227	JT920L	80	4.3	9'-10" (3 m)	1.63 (41 mm)	100' (30 m)
369-056	JT1720	78	8.0	9'-10" (3 m)	2.06 (52 mm)	130' (40 m)
369-235	JT2720	72	8.7	9'-10" (3 m)	2.23 (56 mm)	160' (49 m)
369-052	JT2720	78	8.0	9'-10" (3 m)	2.06 (52 mm)	130' (40 m)
400-168	JT2720 Mach 1	57	7.9	9'-10" (3 m)	2.38 (60 mm)	175' (53 m)
369-221	JT4020	51	9.0	14'-9" (4.5 m)	2.63 (67 mm)	180' (55 m)
369-804	JT4020 Mach 1	46	9.1	14'-9" (4.5 m)	2.81 (71 mm)	190' (58 m)

Fluid Miser™ II



Unlined pipe

